

Descrizione del Prodotto

La stazione di controllo vuota XALK03 di Schneider Electric è progettata per ospitare unità di comando e segnalazione della serie Harmony XB5 con diametro di 22 mm. Realizzata in polycarbonato, presenta una base grigia chiaro (RAL 7035) e un coperchio giallo (RAL 1021). È dotata di tre fori per l'installazione di dispositivi di comando e segnalazione.

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

Specifiche Tecniche

- **Materiale della Custodia:**

Polycarbonato

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Numero di Fori:**

3

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Diametro dei Fori:**

22 mm

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Colore della Base:**

Grigio chiaro (RAL 7035)

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Colore del Coperchio:**

Giallo (RAL 1021)

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-
certified/?utm_source=openai))

- **Dimensioni Esterne:**

Altezza: 136 mm, Larghezza: 68 mm, Profondità: 53 mm

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-
certified/?utm_source=openai))

- **Grado di Protezione IP:**

IP66, IP67, IP69, IP69K

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-
certified/?utm_source=openai))

- **Grado di Protezione NEMA:**

NEMA 4X, 13

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-
certified/?utm_source=openai))

- **Temperatura di Funzionamento:**

Da -40°C a +70°C

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-
certified/?utm_source=openai))

- **Ingressi per Cavi:**

2 fori preforati per cavi da 14 mm e 2 fori preforati per pressacavi Pg 13 o ISO M20 da 12 mm

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal

d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Conformità Normativa:**

EN/IEC 60947-1, EN/IEC 60947-5-1, EN/IEC 60947-5-4, EN/IEC 60947-5-5, JIS C8201-1, JIS C8201-5-1, UL 508, CSA C22.2 No 14
([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Trattamento Protettivo:**

TH
([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Categoria di Sovratensione:**

Classe II secondo IEC 60536
([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Resistenza agli Urti:**

IK03 secondo EN 50102
([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Applicazioni:**

Funzione di arresto di emergenza e spegnimento di emergenza
([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xal
d-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

Certificazioni Ambientali

- **Conformità RoHS:**

Sì

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Conformità REACH:**

Senza sostanze SVHC

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Mercury Free:**

Sì

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

- **Green Premium:**

Prodotto con prestazioni ambientali avanzate

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))

Garanzia

18 mesi

([se.com](https://www.se.com/it/it/product/XALK03/empty-control-station-harmony-xald-xalk-plastic-yellow-3-cutouts-unmarked-2-knockouts-for-cable-entry-ul-csa-certified/?utm_source=openai))